

# Sonofonic™

## Sound Shapes



### Description

Sound Shapes™ take the design of suspended ceiling systems into a new dimension. Manufactured from Sontext's well-known Sonofonic™ sound absorbing Sound panels, Sound Shapes introduce a variety of shapes to ceiling panels, thus allowing the Interior Designer to break free from the constraints of designing to a standardised rectangular ceiling grid pattern. Sonofonic Sound Shapes can be used as a complete ceiling system, or as a localised feature area. Either way, the inherent high performance sound absorbing qualities of Sonofonic panels will enhance the décor of any interior space, and by minimising reverberation or reflected sound, will also provide the occupants with a more comfortable listening and speaking environment.

For more information on the properties of conventional Sonofonic Panels, refer to the Sonofonic Brochure, available from Sontext via the contact details on P.2.

### Colour Range

Sonofonic Sound Shapes can be finished to any Pantone colour on request. Contact Sontext to discuss your requirements.




### Installation

Sonofonic Sound Shapes™ can be fabricated to a large variety of regular, asymmetrical and even three dimensional shapes (see P.2). They may be mounted vertically or horizontally. Regardless of shape, the intrinsic rigidity of the underlying 50mm thick fibrous, light weight insulation also allows the panels to be suspended individually from a ceiling using Sontext's Spiramount™ hangers (in accordance with Sontext Installation Instructions), *without the need for complex furring channel grid systems.*

Examples of recommended layouts for Spiramounts are shown below: 6 mounts minimum are recommended per panel for 2400x1200x50mm panels mounted horizontally, and 2 minimum for 1200x600mm panels mounted vertically. Sontext recommend placing the mounts 100-200mm in from all panel edges to keep the maximum span between fixings to about 1 metre each way, and to help hide them from view.

Contact Sontext for further installation advice.



Recommended Spiramount™ fixing points.


### Sound Performance

Thickness (mm)	Frequency (Hz)	125	250	500	1000	2000	3150	4000	5000	NRC
<b>Sound Absorption Co-efficient</b>										
50mm		0.23	0.64	1.11	1.28	1.22	1.12	1.08	1.05	<b>1.06</b>


Sound Absorption tests were performed to ISO354 (Measurement of Sound Absorption in a Reverberation Room). Sonofonic Panels were tested by Tongji University Institute of Sounds (Shanghai), with a 200mm air gap behind.

## Sonofonic Sound Shapes—Standard Panel Shapes


Panels can be fabricated to virtually any shape up to nominal dimensions of 2400 x 1200mm, including those shown below.




Square




Convex




Hexagon




Trapezoid




Concave



Circle



Left Parallelogram



Right Parallelogram



For further information, contact Sontext Ltd or its Distributors:  
 Sontext Limited  
 71-75 Shelton Street  
 Covent Garden, London, England. WC2H 9JQ  
 Phone: +44 208 144 5191 email: sales@sontextuk.com  
 Website: www.sontextuk.com

